Drayton Lifestyle



2004/108/EC - Electromagnetic compatibility 2006/95/EC – Low voltage CE

BEFORE INSTALLATION

First, make sure the mains supply is switched off!

PROGRAMMER ONLY

The programmer must be set to the type of system it is to control. The link on the back of the unit has two settings – P and G.

- P = a fully pumped and controlled system allowing heating and hot water to be set separately.
- G = a gravity-fed hot water system which does not allow
- independent setting of heating without hot water, though hot water can be controlled alone.

USING AN EXISTING WALL-PLATE

Loosen the securing screws on the old programmer and unplug it. Check that there's 70mm clearance to the right of the wall-plate, and 25mm above it. Check the chart on the next page to compare terminals and if necessary, change the wiring of the wall-plate to suit. Now plug the Lifestyle unit into the wall-plate and tighten the securing screws.

Check the 3A fuse, and switch on the mains.

FITTING A NEW WALL-PLATE

The ideal location is 1.4m above floor level, with reasonable lighting, good access, no condensation, no extremes of temperature, and a supporting surface that fully covers the back of the unit.

Position with 70mm clearance to the right, 25mm above, and sufficient room to access the securing screws underneath.


Fix, with terminals at the top, either direct to a flat wall using wall plugs and No. 6 x 1" (25mm) woodscrews, or on a flush mounting single conduit box type UA1 (BS4662) using M3.5 x 14 bolts. DO NOT USE A SURFACE MOUNTING BOX.

					ç			
MAKE	MODEL Current Mo	Earth Slap	Neutral	Live	Common	NO	Off	Snare
Drayton	Tempus 1, 2 (new models)		Ν	L	1	3	2	4
Lifestyle	LP111, LP711		Ν	L	1	3	2	4
Switchmaster	300		Ν	L	4	1		
	Discontinued/Competence	itors'	Mod	els				
ACL	TC (Towerchron)		2	1	4	7		
Drayton	Tempus 1, 2 (old models)		Ν	L	1	2	3	4
Switchmaster	980		Ν	L	4	1		
Danfoss Randall	TS15, 75 (Mk18)	Е	Ν	L	1	4	2	5/
Danfoss Randall	TS715	Ε	Ν	L	1	4	2	3
Danfoss Randall	TS975	Е	Ν	L	5	4	6	1,2
Danfoss Randall	SET1, SET1E	Е	Ν	L	5	4	6	
Danfoss Randall	SET4	Е	Ν	L	5	4	6	
Danfoss Randall	103, 103E, 103E5, 103E7	4	5	6	3	1		2
Danfoss Randall	911, 971	Е	Ν	L	5	6	4	2
Grasslin Towerchron	QE1		Ν	L	2	4	3	
Grasslin Towerchron	T2001, T2001Q	Е	Ν	L		7		
Honeywell	ST 6100A, ST 6100C		Ν	L	1	4	2	
Honeywell	ST 7000B			L		3	2	
Horstmann	Centaur SC1, SC7		Ν	L	4	3		
Horstmann	Centaur Plus, C11, C17		Ν	L	2	4	3	
Horstmann	Emerald 423, Pearl Auto	Е	Ν	L	3	4		
Horstmann	517, Coronet, H11, H17	Ε	Ν	L	5	4	6	
Landis & Staefa	RWB3		Ν	L		4	3	
Landis & Staefa	RWB30, RWB50, 100, 152, 170		Ν	L	2	4	3	
Landis & Staefa	RWB7	Ν	L	2	4	3	1	
Potterton Myson	EP4000, 4001, 4002, 5002		Ν	L	5	4	2	
Sangamo	M6	Е	4	6	3	1	2	
Smiths	Centroller Mk1, Mk2		Ν	L	3	2		
Smiths	Centroller 30		1	2		4/5		
Smiths	Centroller 300, 980		Ν	L	4	1		
Sunvic	Select 107		Ν	L	1	3	2	4
Sunvic	SP20, SP35		Ν	L	3	5	4	S
Venner	Vennerette		Ν	L	LINE	LOAD		

MAKE	MODEL	Earth	Neutral	Live	H/W off	C/H off	H/W on	
	Current Models							
Drayton	Tempus 6, 7 (new models)		Ν	L	1	2	3	Γ
Lifestyle	LP112, LP241, LP522, LP722		Ν	L	1	2	3	t
Switchmaster	400, 600		Ν	L		4	3	t
	(no connection to terminal 4 on 600)							L
Switchmaster	805		Ν	L	4	2	3	t
	Discontinued/Competitors' Mo	dels						
ACL	MP (Towerchron)		2	1			6	ŀ
ACL	FP (Towerchron)		2	1	8	11	6	t
Drayton	Tempus 3, 4, 6, 7 (old models)		N	L	1	2	3	t
Switchmaster	905, 9001		Ν	L	4	2	3	t
Danfoss Randall	CP15, CP715, FP15, FP715 (Mk18)	Е	Ν	L	1	2	3	t
Danfoss Randall	3020P, 3060	Е	7	6			4	Γ
Danfoss Randall	4033 (link 1-6)	Е	7	6	5	3	4	Γ
Danfoss Randall	102, 102E, 102E5, 102E7 (link 6-3)	Е	5	6			1	Γ
Danfoss Randall	701 (link L-5 and 5-6)	Е	Ν	L			3	Γ
Danfoss Randall	702 (link L-5 and 5-6)	Е	Ν	L	4	2	3	
Danfoss Randall	922, 972 (link L-2 and 2-5)	Е	Ν	L	1	4	3	L
Danfoss Randall	SET2, SET2E, SET3E, SET3M, FP975	Е	Ν	L	3	6	1	ŀ
	SET5 (link L-2 and 2-5)							L
Grasslin Towerchron	DP 72, QE2		Ν	L	1	2	3	Ŀ
Honeywell	ST 699/799 (link L-5 and 5-8)		Ν	L	7	4	6	Ŀ
Honeywell	ST 6200, ST 6300, ST 6400, ST 6450		Ν	L	1	2	3	Ŀ
Honeywell	ST 7100 (link L-3 and 3-6)		Ν	L	7	4	8	Ŀ
Horstmann	525, 527, 425 Diadem, H21, H27,	Е	Ν	L	3	6	1	ŀ
	H121, Tiara (link L-2 and 2-5)			<u> </u>				L
Horstmann	Centaur Plus, C21, C27		Ν	L	1	2	3	Ļ
Landis & Staefa*	RWB2, RWB2E, 20, 40, 102, 200, 252 & 270, RWB9		Ν	L	1	2	3	ľ
Myson	Microtimer (link L-5 and 5-8)		Ν	L	7	4	6	
Potterton Myson	All EP2000's, EP3000's, EP6000's		Ν	L	1	2	3	T
	(link L-5 and N-N)							L
Potterton Myson*	Mini Minder		Ν	L	1	2	3	L
Sunvic	Select 207		Ν	L	1	2	3	Ŀ
Sunvic	SP50, SP100 (link L-3)		Ν	L	1	4	2	

* Can simply be removed from the backplate and replaced without any disturbance to the existing wiring


WIRING THE TIMESWITCH



WIRING THE PROGRAMMER

Make the wiring connections asabove. Note that the output contacts are voltage-free. so power needs to be put on to Terminal 1 either by linking from Terminal L or from a separate supply with a 3A fuse.

USING A DRAYTON SIMP-L-FIT, ALTHOUGH NOT NECESSARY, WILL MAKE THIS INSTALLATION EASIER.



Drayton	Lifestyle	INT	
SINGLE CHANNEL Timeswitch	DUAL CHANNEL Programmer		
or heating OR hot water	for heating AND hot water		
Drepton Liber for UTI for U	Drayton Statut Balance Bala	If the need for to DAY Sorr	
LPIII, LP7II	LP112, LP241, LP522, LP722	Her pro	
SINGLE CHANNEL	DUAL CHANNEL	Swite On It al the you	
User Instructions			

Invensys Controls Sales: 0845 1305522 / Technical Helpline: 0845 1307722 Email: customer.care@invensys.com / Web: www.draytoncontrols.co.uk

What is a programmer?

.. an explanation for householders

Programmers allow you to set 'On' and 'Off' time periods Some models switch the central heating and domestic hot water on and off at the same time, while others allow the domestic hot water and heating to come on and go off at different times.

Set the 'On' and 'Off' time periods to suit your own lifestyle. On some programmers you must also set whether you want the heating and hot water to run continuously, run under the chosen 'On' and 'Off' heating periods, or be permanently off.

The time on the programmer must be correct. Some types have to be adjusted in spring and autumn at the changes between Greenwich Mean Time and British Summer Time.

You may be able to temporarily adjust the heating programme, for example, 'Override', 'Advance' or 'Boost'. These are explained in the manufacturer's instructions.

The heating will not work if the room thermostat has switched the heating off. And, if you have a hot-water cylinder, the water heating will not work if the cylinder thermostat detects that the hot water has reached the correct temperature.



User's Instructions TIMESWITCHES

Lifestyle Timeswitches will automatically control your system by switching it on and off at times that suit you. The light on the front of the timeswitch shows when it's on.

■ LP111 – a 24hr program, up to 3 heating periods each day, and every day the same.

LP711 – a 7-day program, allowing for different timings on each day of the week, up to 3 heating periods each dav.

If the engineer hasn't set your timings for you, your timeswitch will work with a standard program that has been set at the factory. If this doesn't suit you, it's very easy to change it when you've read this introductory section, simply turn to the page for your timeswitch model.



- Make your changes using the SET?, YES/-, and + buttons. Vou can't set ON1 as the last timing before midnight, but you
- can set OFF3 after midnight providing it's not more than 23 hours and 59 minutes after ON1.
- Vou need to set the timings in sequence i.e. ON1, OFF1, ON2, OFF2, ON3, OFF3. If you get out of sequence, the display will flash a warning.

ODUCI	TION Cont
	SWITCHIN
	ON 1 – sta
	OFF 1 – e
	ON 2 – sta
	OFF 2 – e
	ON 3 – sta

future reference.

Y-TO-DAY VARIATIONS

itching on and off the front of the timeswitch there is an Advance/Boost button. allows you to switch your system either on or off, irrespective of he program. So if the heating is off, and you want warmth now, ou can either –

ress Advance to switch it on (ADV will be displayed), and it will tay on until the end of the next period. Or if the heating is on nd you don't need it, press Advance and it will go off until the eginning of the next ON period.

- three hours

Over-riding the program



IMED	=	on for up				
NCE	=	on for 1 p to the en				
N	=	continuo				
les the SELECT buttor						

return to by selecting TIMED.

THE LP111 24hr ELECTRONIC TIMESWITCH

and every day the same. Want to leave a timing as it is? Just press SET? and move on to the next one.

the pre-set program.

The standard program

SWITCHING

- **ON 1** start of first timed
- OFF 1 end of first timed
- ON 2 start of second tin
- OFF 2 end of second tin
- ON 3 start of third timed

Changing the timings

SET

time changes in 10-minute steps.



procedure for ON2, OFF2, ON3 and OFF3.



When you press SET? after setting OFF3, the timeswitch will return to normal operation.

- art of first timed period end of first timed period
- art of second timed period
- end of second timed period
- art of third timed period **OFF 3** – final switch-off of the day

the engineer has set your program and timings – you won't ed to do anything else. Just keep this guide in a safe place

metimes you might need to change the way you use your stem temporarily – perhaps due to an exceptionally cold day. ere's how to do it – without affecting the timings in your

Advance will only operate in TIMED or ONCE modes.

2. Press & Hold Boost to switch on for an extra hour (b1 & BST will be displayed), then Press again for two (b2) or three (b3) hours. To cancel Boost, Press Boost again (bg). Or if the heating is already on, using Boost will extend the ON time by one, two or

At the side of the display there are four operating modes:

- to 3 periods a day
- period a day, from the start of ON1 nd of OFF3.
- usly on.

Use the SELECT button under the flap to change the mode. This won't alter the timings in your program, which you can

LP111 – a 24hr program, up to 3 heating periods each day,

If you need to reset your timings to the standard program

and start again, press 'SET' and '+' together to go back to

Your system will come on for up to 3 heating periods every 24hrs. ON1 starts the first one. OFF1 finishes it, and so on. Notice that ON2 and OFF2 are set to the same time.* This means your system won't respond, but if you want to activate that middle period or change any other timings – read on.

STANDARD PROGRAM
6.30am
8.30am
12.00pm
12.00pm
4.30pm
10.30pm

Press the SET? button and you'll see 'SET PROG?'.

Press the YES button, and you'll see ON1, the start of your first heating period. Adjust it in 1-minute steps using the and + buttons. If the - and + buttons are held down, the

Press SET?, and you'll see OFF1, the end of your first heating period. Adjust this in the same way, press SET?, then repeat the

THE LP711 7-DAY ELECTRONIC TIMESWITCH

LP711 – a 7-day program, allowing for different timings on each day of the week, up to 3 heating periods each day.

Want to leave a timing as it is? Just press SET? and move on to the next one.

If you need to reset your timings to the standard program and start again, press 'SET' and '+' together to go back to the pre-set program.

The standard program

Your system will come on for up to 3 heating periods every 24hrs. ON1 starts the first one, OFF1 finishes it, and so on. Notice that ON2 and OFE2 are set to the same time * This means your system won't respond, but if you want to activate that middle period or change any other timings - read on.

SWITCHING	STANDARD PROGRAM		
SWITCHING	MON-FRI	SAT-SUN	
ON 1 – start of first timed period	6.30am	7.00am	
OFF 1 – end of first timed period	8.30am	9.00am	
ON 2 – start of second timed period*	12.00pm	12.00pm	
OFF 2 – end of second timed period*	12.00pm	12.00pm	
ON 3 – start of third timed period	4.30pm	4.00pm	
OFF 3 – final switch-off of the day	10.30pm	11.00pm	

Changing the timings

Press the SET? button and you'll see 'SET PROG?'.

SET

Set all weekdays First you set the times that are going to be the same for each

weekday, then you can select each day individually and make any further adjustments. If you want each day to be quite different, go straight to 'Set each day'

Press the YES button, and the display will ask 'SET MON to FRI PROG?'

SET

Press YES and you'll see ON1, the start of your first heating period. Adjust it in 1-minute steps using the – and + buttons. If the – and + buttons are held down, the time changes in 10-minute steps

6:30an

Press SET?, and you'll see OFF1, the end of your first heating period. Adjust this in the same way, press SET?, then repeat the procedure for ON2, OFF2, ON3 and OFF3.

8:30an

Set each day

If, after you've set OFF3 you want to fine-tune one or more weekdays, press SET? until you find the first day you want to adjust - then go through the procedure, altering any time you move on to the next of finished, press SET? until you see 'SET SAT SUN PROG?'.

SET

If you don't want to alter any individual days, keep pressing SET? until you see 'SET SAT SUN PROG?'.

Set weekend



Press YES and alter ON1, OFF1, ON2, OFF2, ON3 and OFF3 times in the same way

Set each day

If, after you've set OFF3 for both SAT & SUN, you want to finetune Saturday or Sunday, press SET? until you find the first day you want to adjust - then go through the procedure, altering any time you wish. Press SET? to move on to the next day. When you press SET? after setting your hot water for Sundays, the programmer will go back to normal operation.



If you don't want to alter either day, keep pressing SET? until the programmer goes back to normal operation.

User's Instructions PROGRAMMERS

If the engineer has set your program and timings – you wont need to do anything else. Just keep this guide in a safe place for future reference.

INTRODUCTION

Lifestyle programmers will automatically switch your central heating and hot water on and off at times that suit you. Depending on your system, central heating and hot water can either both come on and off at the same time, or work independently. The light on the front of the programmer shows when each one is on

- There are 4 models in the Lifestyle range:
- LP112 a 24hr program, with linked central heating and hot water on for up to 3 heating periods each day, and every day the same.
- LP241 a 24hr program, with central heating and hot water working independently for up to 3 heating periods each day, and every day the same.
- LP522 a 5/2-day program allowing for different timings at the weekends, with central heating and hot water working independently for up to 3 heating periods each day.
- LP722 a 7-day program allowing for different timings on each day of the week, with central heating and hot water working independently for up to 3 heating periods each day.

If the engineer hasn't set your timings for you, your programmer will work with a standard program that has been set at the factory. If this doesn't suit you, it's very easy to change it when you've read this introductory section, simply go to the section that contains your programmer model.



- Make your changes using the SET?, YES/-, and + buttons on the programmer.
- You can't set ON1 as the last timing before midnight, but you can set OFF3 after midnight – providing it's not more than 23 hours and 59 minutes after ON1.
- You need to set the timings in sequence i.e. ON1, OFF1, ON2, OFF2, ON3, OFF3. If you get out of sequence, the display will flash a warning.

SWITCHING **ON 1** – start of first timed period

- **OFF 1** end of first timed period
- **ON 2** start of second timed period
- OFF 2 end of second timed period
- **ON 3** start of third timed period **OFF 3** – final switch-off of the day

The engineer has set your program and timings – you won't need to do anything else. Just keep this guide in a safe place for future reference.

DAY-TO-DAY VARIATIONS

Sometimes you might need to change the way you use your central heating or hot water temporarily – perhaps due to an unusually cold day, or exceptional demand for hot water. Here's how to do it – without affecting your program.

On the front of the programmer there are two Advance/Boost buttons – one for central heating and one for hot water. They allow you to switch your system either on or off, irrespective of the program. So if the heating or hot water is off, and you want warmth or hot water now, you can either -

- 1. Press **Advance** to switch it on (ADV will be displayed), and it will stay on until the end of the next period. Or if the heating/hot water is on and you don't need it, press Advance and it will go off until the beginning of the next ON period.
- Advance will only operate in TIMED or ONCE modes. 2. Press & Hold **Boost** to switch on for an extra hour (h) & BST will be displayed), then Press again for two (b2) or three (b3) hours. To cancel Boost, Press Boost again (b0). Or if the heating/hot water is already on, using Boost will extend the ON time by one, two or three hours.

Over-riding the program



On each side of the display there are four operating modes one group for central heating, the other for hot water. You can change modes with immediate effect by using the appropriate SELECT button. This won't alter the timings in your program, which you can return to by selecting TIMED.

- OFF continuously off.
- TIMED = on for up to 3 periods a day. ONCE
 - = on for 1 period a day, from the start of ON1 to the end of OFF3.
 - continuously on.

THE LP112 24hr ELECTRONIC PROGRAMMER

LP112 – a 24hr program, with linked central heating and hot water on for up to 3 heating periods each day, and every day the same.

- If the timings haven't been set for you, then your programmer will still be on the factory-set standard 24hr program, with central heating and hot water operating together on the same settings for every day of the week. But it's easy to make changes – just follow the instructions.
- Want to leave a timing as it is? Press SET? and move on to the next one.

If you need to reset your timings to the standard program and start again, press 'SET' and '+' together to go back to the pre-set program.

If you don't press anything for two minutes, the programmer automatically goes back to normal operation.

24hrs, ON1 starts the first one, OFF1 finishes it, and so on Notice that on the standard program ON2 and OFF2 are set

to the same time.* This means your system won't respond,

but if you want to activate that middle period, or change any

STANDARD PROGRAM

6.30am

8.30am

12.00pm

12.00pm

4.30pm

10.30pm

The standard program Your system will come on for up to 3 heating periods every

other timings – read on.

ON 1 – start of first timed period

OFF 1 – end of first timed period

ON 2 – start of second timed period*

OFF 2 - end of second timed period*

ON 3 – start of third timed period

OFF 3 – final switch-off of the day

Press the SET? button and you'll see 'SET PROG?'

Press the YES button, and you'll see ON1, the start of your first

heating period. Adjust it in 1-minute steps using the – and +

Press SET?, and you'll see OFF1, the end of your first heating

When you press SET? after setting OFF3, the programmer will

LP241 – a 24hr program, with central heating and hot water

working independently for up to 3 heating periods each day,

If the timings haven't been set for you, then your programmer

same timings for every day of the week. But it's easy to make

changes, and have heating and water working independently

Want to leave a timing as it is? Press SET? and move on to

If you need to reset your timings to the standard program

and start again, press 'SET' and '+' together to go back to

If you don't press anything for two minutes, the programmer

Your system will come on for up to 3 heating periods every 24hrs.

ON1 starts the first one, OFF1 finishes it, and so on. Notice that on

the standard program ON2 and OFF2 are set to the same time for

respond, but if you want to activate that middle period, or change

both central heating and hot water. * This means your system won't

STANDARD PROGRAM

НW

6.30am

8.30am

12.00pm

12.00pm

4.30pm

10.30pm

CH

6.30am

8.30am

12.00pm

12.00pm

4.30pm

10.30pm

automatically goes back to normal operation.

will still be on the factory-set standard 24hr program, with

central heating and hot water operating together on the

procedure for ON2, OFF2, ON3 and OFF3.

THE LP241 24hr ELECTRONIC PROGRAMMER

Changing the timings

SET

in 10-minute steps.

6:30an

8:30an

return to normal operation.

and every day the same.

iust follow the instructions.

the pre-set program

The standard program

any other timings - read on.

SWITCHING

ON 1 – start of first timed period

OFF 1 – end of first timed period

ON 2 – start of second timed period*

OFF 2 – end of second timed period*

ON 3 – start of third timed period

OFF 3 – final switch-off of the day

Press the SET? button and you'll see 'SET PROG?'.

Changing the timings

SET

SWITCHING

buttons. If the - and + buttons are held down, the time changes period. Adjust this in the same way, press SET?, then repeat the 06490033001 IssH:Invensys B/sheet_TO PRINT 16/9/10 16:26 Page 2

Set the central heating

Press the YES button, and the display will ask 'SET CH PROG?'.

THE LP241 24hr ELECTRONIC PROGRAMMER Cont...



Press YES and you'll see ON1, the start of your first central heating period. Adjust it in 1-minute steps using the – and + buttons. If the – and + buttons are held down, the time changes in 10-minute steps.



Press SET?, and you'll see OFF1, the end of your first central heating period. Adjust this in the same way, press SET?, then repeat the procedure for ON2, OFF2, ON3 and OFF3.



Set the hot water

When you press SET? after setting OFF3 for the central heating, the display will ask 'SET HW PROG?'



- Press YES, then set your times in the same way. Remember, in this mode you can have different times to your central heating if you wish.
- When you press SET? after setting OFF3 for the hot water, the programmer will return to normal operation.

THE LP522 5/2-DAY ELECTRONIC PROGRAMMER

LP522 – a 5/2-day program allowing for different timings at the weekends, with central heating and hot water working independently for up to 3 heating periods each day. If the timings haven't been set for you, then your programmer will still be on the factory-set standard program. This means that central heating and hot water will operate together, with the same timings for weekdays and different ones for the weekend. But it's easy to make changes, and have heating and water working independently – just follow the instructions. Want to leave a timing as it is? Press SET? and move on to the next one.

If you need to reset your timings to the standard program and start again, press 'SET' and '+' together to go back to the pre-set program.

If you don't press anything for two minutes, the programmer automatically goes back to normal operation.

The standard program

Your system will come on for up to 3 heating periods every 24hrs. ON1 starts the first period, OFF1 finishes it, and so on. Notice that ON2 and OFF2 are set to the same time.* This means your system won't respond, but if you want to activate that middle period, or change any other timings – read on.

SWITCHING	WEEK	DAYS	WEEKENDS	
SWITCHING	нw	СН	нw	СН
ON 1 – start of first timed period	6.30am	6.30am	7.00am	7.00am
OFF 1 – end of first timed period	8.30am	8.30am	9.00am	9.00am
ON 2 – start of second timed period*	12.00pm	12.00pm	12.00pm	12.00pm
OFF 2 – end of second timed period*	12.00pm	12.00pm	12.00pm	12.00pm
ON 3 – start of third timed period	4.30pm	4.30pm	4.00pm	4.00pm
OFF 3 – final switch-off of the day	10.30pm	10.30pm	11.00pm	11.00pm

Changing the timings

Press the SET? button and you'll see 'SET PROG?'.



Set the weekday central heating

Press the YES button, and the display will ask 'SET CH MON to FRI PROG?'.



Press YES and you'll see ON1, the start of your first central heating period. Adjust it in 1-minute steps using the – and + buttons. If the – and + buttons are held down, the time changes in 10-minute steps.



Press SET?, and you'll see OFF1, the end of your first central heating period. Adjust this in the same way, press SET?, then repeat the procedure for ON2, OFF2, ON3 and OFF3.



THE LP522 5/2-DAY ELECTRONIC PROGRAMMER Cont...

Set weekday hot water

When you press SET? after setting OFF3 for the central heating, the display will ask 'SET HW MON to FRI PROG?'.



Press YES, then set your times in the same way. Remember, in this mode you can have different times to your central heating if you wish.

Set weekend central heating

When you press SET? after OFF3 for the weekday hot water, the display will ask 'SET CH SAT SUN PROG?'. Press YES to confirm, and alter the times in the same way.



Set weekend hot water

When you press SET? after OFF3 for the weekend central heating, the display will ask 'SET HW SAT SUN PROG?'. Press YES, and follow the procedure.

When you press SET? after OFF3 for HW SAT SUN, the programmer will go back to normal operation.

THE LP722 7-DAY ELECTRONIC PROGRAMMER

LP722 – a 7-day program allowing for different timings on each day of the week, with central heating and hot water working independently for up to 3 heating periods each day.

- If the timings haven't been set for you, then your programmer will still be on the factory-set standard program. This has central heating and hot water operating together – with the option of having different timings for each day of the week. But it's easy to make changes, and have heating and water working independently – just follow the instructions.
- Want to leave a timing as it is? Press SET? and move on to the next one.

If you need to reset your timings to the standard program and start again, press 'SET' and '+' together to go back to the pre-set program.

If you don't press anything for two minutes, the programmer automatically goes back to normal operation.

The standard program

Your system will come on for up to 3 heating periods every 24hrs. ON1 starts the first period, OFF1 finishes it, and so on. Notice that ON2 and OFF2 are set to the same time.* This means your system won't respond, but if you want to activate that middle period, change any other timings – read on.

SWITCHING	WEEK	DAYS	WEEKENDS		
Switchind	нพ	СН	нพ	СН	
ON 1 – start of first timed period	6.30am	6.30am	7.00am	7.00am	
OFF 1 – end of first timed period	8.30am	8.30am	9.00am	9.00am	
ON 2 – start of second timed period*	12.00pm	12.00pm	12.00pm	12.00pm	
OFF 2 – end of second timed period*	12.00pm	12.00pm	12.00pm	12.00pm	
ON 3 – start of third timed period	4.30pm	4.30pm	4.00pm	4.00pm	
OFF 3 – final switch-off of the day	10.30pm	10.30pm	11.00pm	11.00pm	

Changing the timings

Press the SET? button and you'll see 'SET PROG?'.



Set all weekdays

- First you set the times that are going to be the same for each weekday, then you can select each day individually and make any further adjustments. If you want each day to be quite different, go straight to 'Set each day.'
- Press the YES button, and the display will ask 'SET MON to FRI PROG?'.



Press YES and the display will ask 'SET CH MON to FRI PROG?'.



Press YES, and you'll see ON1, the start of your first central heating period. Adjust it in 1-minute steps using the – and + buttons. If the – and + buttons are held down, the time changes in 10-minute steps.



Press SET?, and you'll see OFF1, the end of your first central heating period. Adjust this in the same way, press SET?, then repeat the procedure for ON2, OFF2, ON3 and OFF3.



THE LP722 7-DAY ELECTRONIC PROGRAMMER Cont	SETTING THE CLOCK Con
When you press SET? after setting OFF3 for the weekday central	Set the minute
heating, the display will ask 'SET HW MON to FRI PROG?'.	Press SET?, and the min buttons to set the exact
MORTUE WED THU FRI PROG?	
Press YES, then set your hot water times in the same way. Remember, in this mode you can have different times to your	Press SET?, and 'SET D

Press SET?, and 'SET DA' If you don't want to chang normal operation. If you d

SETTING THE DATE

The weekday is automati the weekday is incorrect



central heating if you wish.

Set each day

PROG?'.

SET

If you don't want to alter any individual days, keep pressing SET? until you see 'SET SAT SUN PROG?'

If, after you've set OFF3 for your hot water, you want to fine-tune

you want to adjust – then go through the procedure, altering any

one or more weekdays, press SET? until you find the first day

time you wish. Press SET? to move on to the next day. When

you've finished, press SET? until you see 'SET SAT SUN



Set weekend

- Press YES, and alter the central heating and hot water times in the same way.
- When you press SET? after OFF3 for HW SAT SUN, the programmer will ask the question TEST? If you want to test your program, see below, otherwise press SET? again. If you don't want to test your program, press SET? again - and you'll be asked the question SET H'DAY? If you want to set a holiday switch off, see page 23, otherwise press SET? again. If you're not going to program in a holiday switch-off, then press SET? again and your programmer will go back to normal operation.

Test your program

- This test facility allows you to run through your program to check
- that the timings are exactly what you want. Answer YES to TEST? and the display will show Monday and
- a time just past midnight. Press YES again and hold it down and the display will start to run through the days of the week, pausing for a few seconds when it reaches an ON or an OFF time. At each pause, the appropriate lights and circuits will come on.
- Release the YES button, and the display will stop running and give you longer to identify a timing.
- Press YES once more, and the display will start running again and will continue all through the week until you press SET?
- Press SET? and your programmer will go back to normal operation.

Remember - The display shows the strict time sequence, so ON1 for HW could be followed by ON1 for CH, then OFF1 for HW etc Using this feature you can program your system to

SET A HOLIDAY SWITCH-OFF

Applicable to all models.

Using this feature you can program your system to switch off while you're on holiday, then switch back on again in time to have the house warm for your return.

- Press SET? three times and you'll see 'SET H'DAY?'
- Press YES to SET H'DAY? and the display will show '00'. Using + and -, set the number of days you want the system to be off
- Press SET, the display will show 'H'DAY' and the programmer will switch off the system. It will then return to normal operation after the set number of days.
- Remember The programmer counts each pass through midnight as a day. So if on a Saturday morning you don't want the heating on again until Tuesday morning, set for 3 days.

SETTING THE CLOCK AND DATE

Applicable to all models.

SETTING THE CLOCK

- The clock in your programmer has been set at the factory, and automatically accounts for British Summer Time. However, should you need to set the clock, read on.
- Press the SET? button until you see SET CLOCK?.

SET

Set the hour

Press YES once, and then the hour will start to flash. Use the - and + buttons to set the hour, checking for AM and PM.

-**12:00**80

Set the month Press SET? and the mo buttons to adjust.	nt
n:Dé	

Ť		
SETTING THE CLOCK Cont Set the minute		WIRING THE PROGRAMMER Cont Connection Charts
Press SET?, and the minutes will start to flash. Use the – and + buttons to set the exact time.		
		ROOM THERMOSTAT Gravity HW, Pumped CH with Room Stats
Press SET?, and 'SET DATE?' appears in the display. If you don't want to change the date press SET? to go back to normal operation. If you do, go on to the next section.		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
SETTING THE DATE		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
The weekday is automatically calculated from the date, so if the weekday is incorrect you'll need to reset the date.		N+> 2 E+> 3 JUNCTION BOX BOILER
Press the SET? button until you see SET DATE?.		Switched and Fused (3A) Mains input 1 2 3 4 5 6 7 8 9 10 11 12 3 4 5 6 7 8 9 10 11 12 2 4 N E 10 11 12 3 4 5 6 7 8 9 10 11 12 2 4 N E 10 11 12 3 4 5 6 7 8 9 10 11 12 2 4 N E 10 11 12 3 4 5 6 7 8 9 10 11 12 2 4 N 11 12 13 12 10 11 12 12 12 12 12 12 11 12 12 12 12 12 12 13 12 12 13 12 13 <th13<< th=""></th13<<>
SET.		<pre> For pump overrun boilers consult manufacturer's instructions See Thermostat Key </pre> LWC3
Set the yearPress YES and the year will start to flash. Use the – and + buttons to adjust.		
		Mid-Position Valve System
 Set the month Press SET? and the month will start to flash. Use the – and + buttons to adjust. 		ROOM THERMOSTAT PROGRAMMER CYLINDER THERMOSTAT BTS 182 ELNCH SET TO * SCH
		$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
Set the day■ Press SET? and the day will start to flash. Use the – and + buttons to adjust.		#- LINK L-1 FOR 230V OUTPUT JUNCTION BOX 1 2 3 4 5 6 7 8 9 101112 3 - F
		$LWC3 \qquad \qquad \qquad 7 \leftarrow L$
 Set the Day Light Saving Press SET? and the current DLS status will start to flash for day light saving (British Summer Time). Use the – and + buttons to 		E • → 3 A A A A Switched and Fused (3A) Mains input W GR OR BL YG BOILER MID-POSITION VALVE 3 ← E 2 ← N
turn on or off.		LIFESTYLE 679H340-30L0 (22mm) 7 - L LIFESTYLE 779H340-30L0 (28mm) DRAYTON FLOWSHARE 2 † For pump overrun boilers consult V4073A
,		manufacturer's instructions Landis & Gyr * See Thermostat Key MAV 3
Press SET? to go back to normal operation.		
USERS NOTES		
		Spring-Return 2-Valve System
		ROOM THERMOSTAT PROGRAMMER CYLINDER THERMOSTAT
		$\begin{array}{c c c c c c c c c c c c c c c c c c c $
		$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
		#- LINK L-1 FOR 230V OUTPUT JUNCTION BOX 1 2 3 4 5 6 7 8 9 1 01 1 1 2 PUMP
		$LWC3 \qquad 7 \downarrow \\ \downarrow \bullet \rightarrow 1 \qquad 1 \qquad 7 5 2 3 \qquad 1 7 6 2 3 \\ \downarrow \bullet \rightarrow 2 \qquad A A A A A A A A A A$
		Image: bold relation of the set of the
		LIFESTYLE 679H308-30L1 7 LIFESTYLE 779H33530L10 DRAYTON ZV22
		Honeywell Honeywell Honeywell Honeywell Marios 2022 Honeywell Marios Marios Honeywell Landis & Gyr
		* See Thermostat Key ZAV222
		Make the wiring connections, as above, for the appropriate system.
		For surface wiring, snap out the cable entry strip on the bottom edge of the wall-plate. Lifestyle units are double-insulated and need no earth connection, but an earthing continuity (loop) terminal is provided for convenience.
		After wiring, plug in the unit and tighten the securing screws. Check the mains input has a 3A fuse, and switch on the mains. Then set the timings as shown in the User's Guide.
		ALWAYS SWITCH OFF THE MAINS BEFORE REMOVING THE LIFESTYLE TIMESWITCH/PROGRAMMER - AND NEVER FIT IT TO A LIVE WALL-PLATE!
	Invensys Controls Sales: 0845 1305522 / Technical Helpline: 0845 1307722 Email: customer care@invensys.com / Web: www.dravtoncontrols.co.uk	Invensys Controls Sales: 0845 1305522 / Technical Helpline: 0845 1307722 Email: customer.care@invensys.com / Web: www.dravtoncontrols.co
1	Email: customer.care@invensys.com / Web: www.draytoncontrols.co.uk	Email: customer.care@invensys.com / Web: www.draytoncontrols.co.
\frown		

