

shower valves - Plus Thermostatic Concealed Shower

Introduction

The Plus combines a clean, simple style with Inta's thermostatic protection. Practical and elegant, the Plus range can be used to enhance the appeal of the bathroom setting whilst protecting those who use the bath or shower.

gives total control



- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Temperature stability of ± 2°C
- Fail safe protection on both the hot and cold supplies
- Operating pressure range of 0.2 to 5 bar
- WRAS and TMV2 approved

Product Range

Description	Code
Plus thermostatic concealed shower with flexible slide rail kit	20015665CP
Plus thermostatic concealed shower	20015.1CP
Flexible slide rail kit	31665CPA









shower valves - Plus Thermostatic Concealed Shower

Features

Technical Specification

Max Inlet Pressure (static)	5 Bar
Min Inlet Pressure (dynamic)	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections	22mm compression elbows
Outlet Connections	22mm compression
Min Temperature differential to achieve hot or cold failsafe	15°C

System Installation: Unvented, Pressurised, Gravity and Combination Boilers













