Approvals:

BEAB Approved

BEAB



CE

3yr Guarantee

WRAS Approved

The Contour 7000 range.

Key features

- 7 litre capacity, point of use
- Adjustable thermostat 15C 75C
- Integral on/off and flow control
- · Frost protection setting · Choice of heat settings
- · Ideal handwash and dishwash temperature settings indicated on the unit
- Tamperproof thermostat cover •
- · Range of vented taps available for installation under sink

- Range of vented taps available for installation
 Complete with 300mm swivel spout
 Proven long life copper element
 Negligible standing heat loss
 Extended swivel spout 450mm 84-780404
 Extended swivel spout 600mm 84-780405
 Monoblock chrome mixer 84780408
 Extended swivels hear (venter) 0020000

- Extended flexible hose (2metres)- 83762502

The range


The Contour 7000 has a 7 litre capacity of hot water storage for oversink washing needs. Using the monoblock chrome accessory it can be fitted undersink. Alternatively the Contour 7000 Remote is a complete installation pack for undersink fitting, featuring an air operated sink mounted switch that when pressed delivers hot water through a remote swivel spout at your pre-set temperature. These units also benefit from minimal standing heat loss because they are installed at point of use.

Product variations

Product reference	Short code	Catalogue number	KW loading @ 240V	Recommended cable size	Re
Contour 7000 3KW	C73	44784001	ЗКW	2.5mm ²	13
Contour 7000 1KW	C71	44784002	1KW	1.0mm ²	5a
Contour 7000 Remote	C7U3	44784020	3KW		13



REDRING



3amps Samps 3amps

