Magnetic Heating Filter

Honeywell





Protect and increase the life of the heating system

Installing a Honeywell Heating Filter will help to maintain an efficient and healthy heating system. The powerful neodymium magnet will capture metallic particles in the water flow (black sludge) and the cleverly designed filter mesh will trap dirt and other non-metallic particles which could cause long term damage.

Features and Benefits

- Can be installed on any domestic heating system
- Rotating connector allows for installation on vertical or horizontal pipework
- Easy to install and maintain: reduce maintenance calls
- · Powerful neodymium magnet
- · Can be used as a water treatment dosing point
- · Stainless steel filter mesh for non-magnetic contamination
- Removable sheath makes cleaning easier
- Pipe cutter guide to assist installation
- Easy to read installation instructions
- 1. Filter mesh 2. Removable sheath to easily clean the magnet
- 3. Filter chamber 4. Magnet





Technical Data:

Horizontal

positioning

- Medium: Water: Water + Glycol
- Operating pressure max. 4 bar
- Temperature range 5°C 90°C
- Connection sizes 22 mm & 28 mm compression fittings

Materials:

- Polyamide filter housing
- Polyamide glass-fibre reinforced diverter body, ring and magnet housing
- Stainless steel filter mesh EPDM sealing washers
- Neodymium magnet (tested) according to IEC 60404-5 & ASTM A977)

Part No.	Size
MHF49-22A	22mm
MHF49-28A	28mm



Honeywell

Honeywell House, Bracknell Berkshire, RG12 1EB Tel: 01344 656000 Fax: 01344 656240

E-mail: insidesales@honeywell.com

www.honevwelluk.com

© 2015 Honeywell International Inc. All rights reserved.

EN3H-3205-LIK01-R0215