

AFTERCARE INSTRUCTIONS

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting, even the non-scratch cleaners. **NOTE: Never use abrasive detergents or disinfectants or those containing alcohol, hydrochloric acid or phosphoric acid.**

Bristan recommend E-Cloth for cleaning all of our bathroom & kitchen products. Using just water, E-cloth gives a smear free, deep clean by breaking up and holding dirt, which normal cloths leave behind. Order through your Bristan stockist. (ORDER CODE: ECLOTH)



GUARANTEE

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture.

NOTE: The 5-year guarantee on the cartridge is invalidated if damaged by any waterborne debris.

All products must have access for servicing or replacement during the life of the product.

In the interests of continuous product development we reserve the right to alter specification as necessary

PRODUCT CODE: PM 1HBF C

PRODUCT IDENTIFICATION CODE LASER ETCHED ON PRODUCT
Installer please fill in code here _____.(Where applicable)

TELEPHONE HELPLINE: 0844 701 6273

Bristan Group Limited
Birch Coppice Business Park
Dordon
Tamworth
Staffordshire
B78 1SG
UK
A Masco Company
Website: www.bristan.com
Telephone: 0844 701 6274
Facsimile: 0844 701 6275
Email: enquire@bristan.com

BRISTAN

Prism One Hole Bath Filler

Fitting Instructions & Contents List

Please keep these instructions for future reference and request of replacement part

WATER PRESSURE

This mixer is suitable for use at all supply pressures 0.2 bar to 8 bar. However for optimum use both hot and cold supplies should be reasonably balanced.

Operating Pressures: Min 0.2 bar, Max 8.0 bar.

If the tap is installed at low pressure (tank fed), then the minimum height from the outlet nozzle to the underside of the cold tank should be at least 2 metres to ensure adequate performance.

These taps should be installed in compliance with the Water Regulations. Where the supplies are unbalanced, i.e. hot water from cylinder tank / cold from the mains, approved check valves must be fitted in the supply pipes.

INSTALLATION

1. Identify all components and check for completeness, particularly before commencing installation.
2. Fix the mixer body to the bath using the full rubber washer (6) between the fitting and the bath, and the 'C' shaped rubber (7) and metal washers (8) on the underside of the bath, to be secured by the nut (9) and threaded rod (10).
3. Fit the tail pipes (11) by **HAND ONLY (DO NOT OVERTIGHTEN)** to the fitting and Connect the hot and cold supplies.
4. Fully open the mixer in its mid position, letting it run for a few minutes to flush the system.
5. Check all joints and connections for leaks.

MAINTENANCE

If the fitting begins to drip:

1. Turn off the water supply
2. Prise out handle cap (12), loosen grub screw (13) and lift off the head (1).
3. Unscrew shroud (2) and brass retaining nut (3) and lift out the cartridge (4) complete with seal.
4. Clean or replace cartridge, clean and grease seal and refit.

NOTE: That there are locating pins on the bottom of the cartridge that fit in Holes inside the tap, to ensure it is fitted the right way round.

5. Refit the handle and tighten the grub screw. Replace the lever.
6. If problem persists, contact our helpline quoting the product code.

