



TYBOX 137

Wireless programmable thermostat for boiler or non-reversible heat pump -
2 levels of settings - transmitter + RF receiver

6053007 - TYBOX 137 -

Benefits

- Elegant design with large backlit screen
- Can be installed away from the boiler in the most suitable room for taking the temperature, thanks to the wireless technology
- Prevents handling errors thanks to the programs and settings lock function
- Maximises savings thanks to the accuracy of the programming, to the nearest ¼ hour, ½ hour or hour

Functions

Intelligence Range

- Choice from 2 adjustable temperatures from 5 to 30°C: Comfort, Reduced
- Daily or weekly programming, which can be customised using a switch
- Quick selection of operating modes using the selector dial:
 - On/Off/Auto
 - Holiday program with built-in calendar
 - Reminder of the annual maintenance service
 - Automatic time change: summer/winter
 - Calibration of the temperature sensor
 - Hourly display of the boiler operating time (excluding DHW)

Features

- Power supply of the room unit: 2 LR03 batteries (supplied)
- Power supply of the receiver: 230 V
- Length of the receiver cable: 2 m.
- Dry contact output: 5 A
- Control range from 5° to 30°C
- Regulation base time can be set from 15 minutes to 1 hour

Further solutions

Link the following options to your programmable thermostat:

- The wireless door/window opening detector for switching

from heating to Frost Protection mode upon opening a window
- A PSTN or GSM telephone remote control for remote control of the heating