TECHNICAL DATA SHEET

COLONIAL

Thermostatic Surface Mounted Shower Valve With Rigid Riser

Product Specification

Product Code: KN2 SHXRR C Finishes: Chrome Product Type: Traditional

Construction: Body is of Brass Construction

Cartridge Type: Thermostatic

Suitable for all plumbing systems, Supply:

preferably balanced

Inlet Connections: 15mm Compression Elbows

Outlet Connections: G1/2"

Water Pressure: Min 0.1 bar Max. 5.0 bar Dimensions: 110-155mm inlet centres

Additional Information

- •Single Lever Control flow and temperature are controlled by an easily operated single lever handle
- •Thermostatic cartridge maintains showering temperature to +/- 1 degree
- •Automatic shut-off in the event of hot or cold water supply failure, thus reducing the risk of injury
- Factory set to a maximum of 43oC to eliminate the ability to select on unsafe temperature. Can be adjusted to user preference.
- •Supplied with riser rail and 4" shower rose
- •Uses swivel inlet elbows with 110-155m centres. Valve can be fed from top, bottom or rear
- •Chrome plated to BS EN 248

Flow Rates (litres per minute)

System Pressure	0.1bar	0.2bar	0.5bar	1.0bar	2.0bar	3.0bar	5.0bar
With Flow Regulators				6.7	7.2	7.5	7.8
Without Flow Regulators	7.07	10	15.8				

Compliance / Approvals

WRAS Approval No: 1404020 TMV2 Approval No: BC1294/1013 TMV2 Designations: HP-SE and LP-S

Technical Advice: For further information please call 0844 7016273

or email customercare@bristan.com

Guarantee: 5 years covering manufacturing faults.







Max. 10

Max. 13



BRISTA









www.europeanwaterlabel.eu

water

label