TECHNICALDATASHEET

BRISTAN

PRISM
PRISM TWINLINE THERMOSTATIC SHOWER VALVE WITH ADJUSTABLE RISER (CEILING FED)

ProductSpecification

|	
Product Code:	PM TLSHX C
Finish:	Chrome
Product Type:	Contemporary
Construction:	Body is of brass construction
Cartridge Type:	Thermostatic cartridge
Supply:	Suitable for all plumbing systems, preferably balanced
Inlet Connections:	15mm compression connections with built in isolations
Outlet Connection:	G ½"
Water Pressure:	Min 0.1bar, Max. 10.0bar

Anti Scald safety feature
Cold water feed encases hot to ensure safe temperature

Ceiling Fed Detail

© Bristan Group 2009

125
965
100
112
1480 (Max)
259

AdditionalInformation

- Dual control – Flow and temperature are controlled separately giving accurate control of both.
- Thermostatic cartridge maintains showering temperature to +/- 1ºC by compensating for changes in the incoming water temperature and pressure giving the stable outlet temperature.
- Automatic shut off in the event of hot or cold water supply failure, thus reducing the risk of scalding.
- Factory set to a maximum of 43ºC to eliminate the ability to select an unsafe temperature – this is adjustable to suit user preference
- Shower can be fitted directly to solid walls, or pre-tiled wall. Shower is ceiling fed and cold water feed encases hot to prevent riser from getting hot.
- Supplied with integral riser rail, 1.5m shower hose, hose retainer and single function handset with rub clean nozzles.
- Chrome plated to BSN 248.

Technical Advice:	For further information please call 0844 7016273 or email customercare@bristan.com.
Guarantee:	5 years covering manufacturing faults.

FlowRates (litres per minute, open outlet)

SystemPressure	0.1bar	0.5bar	1bar	2bar	3bar
PM TLSHX C	7.0	16.5	22.0	31.0	40.0
With Flow Limiters Fitted	-	11.0	11.0	11.0	11.0

5 YEAR PRODUCT GUARANTEE
24 NEXT DAY DELIVERY SERVICE
0844 7016273 SUPPORT HOTLINE

D3