TECHNICAL DATA SHEET

REGENCY

Thermostatic Surface Mounted Shower Valve With Adjustable Riser

Product Specification

Product Code: Finishes: Product Type: Construction: Cartridge Type: Supply:

Inlet Connections: **Outlet Connections:** Water Pressure: Dimensions:

R2 SHXAR C Chrome Traditional Body is of Brass Construction Thermostatic Suitable for all plumbing systems, preferably balanced 15mm Compression Elbows G1/2" Min 0.1 bar Max. 5.0 bar 110-155mm inlet centres

Additional Information

- Dual Control Flow and temperature are controlled separately giving accurate control of both
- •Thermostatic cartridge maintains showering temperature to +/- 1 degree
- •Automatic shut-off in the event of hot or cold water supply failure, thus reducing the risk of injury
- •Factory set to a maximum of 43oC to eliminate the ability to select on unsafe temperature. Can be adjusted to user preference.
- •Supplied with riser rail, 1.5m hose, hose retainer and a single function handset
- Supplied with 155mm pair of swivel inlet elbows. Valve can be fed from top, bottom or rear
- •Chrome plated to BS EN 248

Flow Rates (litres per minute)

System Pressure	0.1bar	0.2bar	0.5bar	1.0bar	2.0bar	3.0bar	5.0bar
With Flow Regulators				7.6	7.6	7.6	7.6
Without Flow Regulators	5.59	7.9	12.49				

Compliance / Approvals

WRAS Approval No: TMV2 Approval No: TMV2 Designations:	1404020 BC1294/1013 HP-SE and LP-S
Technical Advice:	For further information please call 0844 7016273
	or email customercare@bristan.com
Guarantee:	5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: www.bristan.com Email: enquire@bristan.com







www.europeanwaterlabel.eu

water label

L/Mi

Max. 10 Max. 13

D3

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

BRISTAN

