

Your Bristan bathroom accessories have a high quality finish and should be treated with care to preserve the visible surfaces. All surface finishes will wear if not cleaned correctly, the only safe way to clean your accessory is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning products will damage the surface of your fitting - even non-scratch cleaners.

## **GUARANTEE**

At Bristan, we want to make things as easy as possible for our customers. That's why we design products that are easy to fit and use, and that are quality tested to make sure they won't let you down. It's also why we offer solid guarantees on all products, effective from the date of purchase, to give you peace of mind.

All Bristan accessories are covered by a **5year guarantee** covering parts. This guarantee is in addition to your statutory and other legal rights. For full terms and conditions, please visit [www.bristan.com/guarantees](http://www.bristan.com/guarantees)

*In the interests of continuous product development we reserve the right to alter specification as necessary.*

## **Need help?**

Please contact **Bristan Care Customer Service on 0844 701 6273**. Please also call this number in the unlikely event that you encounter any problems with the product during the guarantee period.

Bristan Group Limited  
Birch Coppice Business Park  
Dordon  
Tamworth  
Staffordshire  
B78 1SG

Telephone: 0844 7016273  
E:mail:[enquire@bristan.com](mailto:enquire@bristan.com)

(FI BRI ACC)

(Rev.D1)

## **Bathroom Accessories**

## **Fitting Instructions**

**Please keep these instructions for future reference**

Congratulations on purchasing Bristan Bathroom Accessories. You are now the owner of a high quality product, manufactured to exacting standards. Fitting your accessories is easy when you follow these instructions. Please identify all components and check for completeness, particularly before arranging fitting.

### Single Backplate Fitting

1. Establish the position for the accessory and mark out the fixing holes. (Fig. 1)
2. Drill holes to suit, and insert wall plugs if required.
3. Screw the fixing plate to the wall, with the back flat to the wall. (Fig. 2)
4. Loosen off the grub screw (but do not remove) and place the accessory over the fixing plate with the grub screw at the bottom.
5. Tighten up the grub screw until the pillar is secure against the wall.

**NOTE:** All centers should be measured and checked prior to drilling.

### Double Backplate Fitting

1. Establish the position for the accessory and mark out the fixing holes; It is recommended that the centre distance of the accessory assembly is checked prior to drilling.
2. Drill holes to suit and insert wall plugs if required.
3. Screw the fixing plates to the wall, with the back flat to the wall. (Fig. 2)
4. Loosen off the pillar grub screws, but do not remove.

### Towel Rail

1. Fit the towel rail to the end pillars and place them over the fixing plate with the grub screws at the bottom.
2. Tighten the grub screws until the pillars are secure against the wall.

### Shelf

1. Fit shelf into the brackets and secure in position by tightening the plastic grub screws in the pillars.
2. Check shelf for security.

### Extending Mirror

1. Establish the position for the mirror and mark out the fixing holes.
2. Drill holes to suit and insert wall plugs if required.
3. Screw the fixing plates to the wall, with the back flat to the wall. (Fig. 2)
4. Loosen off the wall bracket grub screws but do not remove.
5. Place the wall bracket over the fixing plates with grub screws at the bottom.
6. Tighten the grub screws until the wall bracket is secure against the wall.
7. Screw mirror down onto extending bracket and check for security.




FIG.1



FIG.2

**NOTE:** Depending on your accessory, the shape of the backplate (where supplied) may vary.

### Wire Baskets

1. Establish the position for the accessory and mark out the fixing holes;
2. Check the position of the marked holes with shelf the assembly prior to drilling.
3. Drill holes to suit and insert wall plugs if required.
4. Ensure that the brass threaded washers provided, sit between the accessory and the screw head, and fit screws accordingly. (see Fig.3)
5. Fit concealing caps over screw heads and check basket for security.




FIG.3