TECHNICAL DATA SHEET

BRISTAN

COMMERCIAL

Gummers 22mm Thermostatic Mixing Valve

Product Specification

Product Code: Finishes: Product Type: Maximum Hot Temperature: Supply:

Inlet Connection:

Outlet Connection:


Working Pressures:

TS4753ECP Chrome Commercial 80oC Suitable for all plumbing systems, preferably balanced 22mm 22mm Min 0.1 Bar, Max 5.0 Bar

Additional Information

- •Ideal for group applications at pressures as low as 0.1bar
- •Compatible with non-thermostatic showers & taps, timed flow controls, and Pulse 8 automatic controls
- •Temperature control can be locked in position or allow adjustments
- •Factory pre-set maximum temperature at 43oC
- •Automatic shut-off in the event of hot or cold water supply failure
- •Check valves, and serviceable filters as standard
- •Operates at a maximum pressure differential of 10:1
- •Recommended for Healthcare, Education or Sports & Leisure environments





115

Flow Rates (litres per minute)

System Pressure	0.1bar	0.2 bar	0.5 bar	1.0 bar	2.0 bar	3.0 bar	5.0 bar
Open Outlet	14.8	20.91	33.07	46.77	66.14	81	104.6

Compliance / Approvals

WRAS Approval No:	1403025
TMV3 Certificate No:	BC1314/0415
TMV3 Designations:	HP-T44 and LP-T44
Complies with NHS D08 Spe	ecifications

Max. 13 **Technical Advice:** For further information please call 0844 7016273 or email customercare@bristan.com www.europeanwaterlabel.eu Guarantee: 1 year covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: www.bristan.com Email: enquire@bristan.com





water label

1.///

D3

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.