RTA

Take control, the right temperature all the time, easy to install, easy to use

Benefits

+ **Quick and easy to install.**
+ **Easy to turn rotary control, easy to set.**
+ **Visual indication of the setting temperature.**
+ **LED to indicate heating state.**
+ **Accurate temperature control.**
+ **Energy savings.**
+ **Hard wired version.**

NEOMITIS

Designed in France

WARRANTY **3** YEARS

3 years warranty

Stylish and slim

ERP class 1

Energy class

RTA online

Easy to install   Easy to use   Wired

In a few words ...

This analog room thermostat has been designed for easy installation and is intended to make your life easier and more comfortable. With a simple rotary dial it uses electronic technology to measure temperature and control the heating output.

Temperature setting easy to select

Limit and lock

Features

- Room temperature control.
- 2 knock out areas for wiring.
- Limit and lock temperature setting.
- Two choices of installation: on connection box or surface mounting.
- Mounting on standard wall box.
- Frost protection at 7°C.
- Temperature setting from 7°C to 30°C.
- Operating status LED.

Technical specifications

- White plastic housing RAL 9016.
- Installation on connection box or surface mounting.
- Type of control: 2 point switching (ON/OFF).
- Environment:
  - IP20.
  - Operating temperature: 0°C to +40°C.
  - Setpoint temperature: +7°C to +30°C.
  - Storage temperature: from -10°C to +60°C.
  - Humidity: 80% at +25°C (without condensation).
- Manufactured on ISO 9001 V2008 certified site.
- Standards:

LVD	EMC	RoHs
EN60730-1; EN60730-2-9; EN62311	EN60730-1; EN60730-2-9	EN50581

$C\,E$

Model	Reference	Designation	Height (mm)	Width (mm)	Depth (mm)
RTA	RTAa	Wired analog room thermostat	91	84	27,5