Wired smart digital room thermostats .

boiler+ compliant

RT7PLUS

Smart digital room thermostat with automation and optimization features

NEW





Designed in France



3 years warranty



Stylish and slim



Suitable for all heating applications



PID technology



Energy class



RT7PLUS











Easy to install

In a few words ...

This digital room thermostat has been designed for easy operation and is intended to make your life easier and help you save energy and money. The extra large LCD and ambient temperature digits mean that the display can be read from across the room and the simple rotary dial makes it the perfect for everyone who wants a digital thermostat that is easy to understand.

The slide control operation and simple programming method means that everyone can set their own convenient schedule for each day of the week. Having the ability to customise each day of the week allows for greater efficiency savings. The dual optimization feature allows you to optimize your programming by favouring comfort or savings. This digital thermostat is just one of a range of products that can provide the right solution for controlling your heating system in an easy and efficient way, whether it is a new installation or an improvement to an existing one.

Boiler Plus compliant features

I Automation:

- Single day or multiday programming
- Programmable comfort periods.

| Dual optimization:

OPTI ECO or OPTI COMFORT, we design smart products to make your life easier. Optimize your programming by favouring comfort or savings:

Depending on various parameters: room inertia, ambient temperature, desired temperature, the thermostat calculates and optimizes the programming for each heating period whether set to Comfort or Savings (Eco):





Features

- White backlit display.
- Room temperature control.
- Operating modes: Auto, Comfort, Eco, Heating on Standby with frost protection.
- Boost function for 1 hour: temporary Comfort temperature.
- Programme lock.
- Service interval function.





I Technical specifications

- White plastic housing RAL 9016.
- 2x AA (LR6) batteries supplied 2 years typical life.
- Wall mounting plate supplied.

Type of control:

- 2 point switching (ON/OFF).
- PID (Proportional Integral Derivative).
- Relay output: 5(2)A.

| Environment:

- IP30.
- Operating temperature: 0°C to +40°C.

- Setpoint temperature: +5°C to +30°C.
- Storage temperature: from -10°C to +60°C.
- Humidity: 80% at +25°C (without condensation).
- Manufactured on ISO 9001 V2015 certified site.

Standards:

LVD	EMC	RoHs
EN60730-1; EN60730-2-9; EN62311	EN60730-1; EN60730-2-9	EN50581

Models	References	Designations	Heights (mm)	Widths (mm)	Depths (mm)
RT7PLUS	RTE7C	Wired 7 day programmable digital room thermostat	95	120	29,6
RT7BPLUS	RTE7BC	Wired 7 day programmable digital room thermostat - black version	95	120	29,6

