## RTM

Take control, the right temperature all the time, easy to install, easy to use





2 years warranty











## In a few words ...

The wired mechanical room thermostat is extremely easy to install, has an innovative and ergonomic design. It was designed to make your life easier and help you to save money on your heating bills. It directly regulates room temperature and controls the heating/cooling circuit which is connected to it.



## **Features**

- Room temperature control.
- Mounting on standard wall box.
- L Frost protection at 5°C.
- Temperature setting from 5°C to 30°C. I.
- Visual indication of the setting temperature. L



**F** 

## Technical specifications

- White plastic housing: RAL 9016.
- Wall mounting installation.
- Line voltage : 24-250V.
- Capacity of the contacts: 16(2.5)A 250V AC.
- Sensitive element: vapour expansion belows.
- I Type of control: ON/OFF.
- Environment:
  - IP20.
  - Operating temperature: 0°C to +50°C.
  - Setpoint temperature: +5°C to +30°C.

- Storage temperature: from -10°C to +60°C.
- Manufactured on ISO 9001 V2015 certified site.

Standards:

LVD	EMC	RoHs
EN60730-1; EN60730-2-9; EN62311	EN60730-1; EN60730-2-9	EN50581

Model	Reference	Designation	Height (mm)	Width (mm)	Depth (mm)
RTM	RTMa	Wired mechanical room thermostat	71	71	39

Tel: +44 (0) 2071 250 236 - Fax: +44 (0) 2071 250 267 - E-mail: contact\_uk@neomitis.com

Pictures and technical specifications are not contractual and given as an indication. Specifications may change depending on product development. Néomitis keeps the right to change without notice. All rights reserved - Photo credits : © Fotolia