


evolve

High efficiency
system boilers




- EVOLVE SYSTEM 18S - 35S ■
- ErP CLASS A (94%) ■
- NG/LPG OUT OF THE BOX ■
- 7:1 MODULATION RATIO ■
- LIGHTWEIGHT WITH COMPACT DIMENSIONS ■
- ACC (ACTIVE COMBUSTION CONTROL) ■
- 7 - 10 YEAR WARRANTY ■

evolve S

High efficiency system boilers

Dimensions (mm)



* Depth for models 18S & 24S

**Depth for models 30S & 35S

- Fully compliant with the Energy-related Products Directive. Further efficiency can be achieved when installed with a weather compensation sensor or OpenTherm control.
- ACC (Active Combustion Control) reduces emissions by adapting the air/gas mix according to the gas quality.
- Efficiency indicator with on screen display of "High" or "Optimal" efficiency.
- NG/LPG compatible out-of-the-box, with no additional kit required.
- 7-10 year parts and labour warranty.⁽¹⁾
- Compact dimensions enable the boiler to be sited almost anywhere in the home, including within a kitchen cupboard.⁽²⁾
- Text driven menu for easy set up and adjustment.
- Exceptional modulation ratio of 7:1 maximises efficiency and comfort for end user.
- Designed for easy installation.
- The easy to use appliance interface and controls permits the end user to view, change and adjust the operating modes of the boiler.
- Versatile flue options with concentric flue lengths up to 11m.
- Direct rear flue option, reduces overall installation footprint.
- Built-in frost protection, protects the appliance from damage during periods of cold weather.
- Simple commissioning; only minimal adjustments are required after installation and automatic modulation eliminates the need to range rate the boiler.
- Anti-seize function protects the pump and motorised valve from sticking during long periods of inactivity.
- Self-start programming protects the pump and motorised valve from sticking during long periods of inactivity.
- Enhanced Autostop disabling function with four optional modes of operation, including: service reminder, reducing the output of the boiler and moving the boiler into standby mode.⁽³⁾

⁽¹⁾ Subject to registration and annual service. 10 year warranty offer valid when installed with BeSMART and registered through Vokèra Affinity, terms and conditions apply. ⁽²⁾ Cupboard fit applies to 18S & 24S. ⁽³⁾ Autostop activation device required.

| SPECIFICATIONS | 18S | 24S | 30S | 35S |
|--|----------|----------|----------|----------|
| PRODUCT ORDER CODE | 20127447 | 20127448 | 20131081 | 20131082 |
| CENTRAL HEATING | | | | |
| HEAT INPUT (kW) | 18 | 24 | 30 | 35 |
| MAXIMUM HEAT OUTPUT 80/60°C (kW) | 17.6 | 23.5 | 29.4 | TBC |
| MAXIMUM HEAT OUTPUT 50/30°C (kW) | 19.2 | 25.6 | 31.8 | TBC |
| DIMENSIONS | | | | |
| HEIGHT (MM) | 740 | | | |
| WIDTH (MM) | 420 | | | |
| DEPTH (MM) | 275 | | 350 | |
| WEIGHT | | | | |
| DRY WEIGHT (KG) | 34.4 | 34.4 | 35.5 | 38.5 |
| CONNECTIONS | | | | |
| FLOW & RETURN | 22MM | | | |
| GAS | 15MM | | | |
| SAFETY VALVE | 15MM | | | |
| ELECTRICAL | | | | |
| VOLTAGE (V/Hz) | 230/50 | | | |
| FLUE DETAILS (CONCENTRIC) | | | | |
| MAXIMUM HORIZONTAL FLUE LENGTH 60/100MM | 10M | | 8M | |
| MAXIMUM VERTICAL FLUE LENGTH 60/100MM | 11M | | 9M | |
| EFFICIENCY | | | | |
| ErP SEASONAL SPACE HEATING ENERGY EFFICIENCY (CLASS/%) | A/94 | | | |
| NOX CLASS | 6 | | | |

ACCESSORIES

| DESCRIPTION | CODE |
|--|----------|
| STANDARD HORIZONTAL FLUE TERMINAL (XF) | 20122759 |
| TELESCOPIC HORIZONTAL FLUE TERMINAL (XT) | 20122761 |
| VERTICAL FLUE TERMINAL (XV) | 20122763 |
| REAR FLUE TERMINAL | 29450133 |
| 7 DAY RF PROGRAMMABLE ROOM THERMOSTAT | 20101743 |
| OUTSIDE WEATHER COMPENSATION SENSOR | 2359259 |
| MAGNETIC FILTER | 29450199 |
| CONDENSATE PUMP | 404 |



Space Heating Efficiency Reduced Emissions ACC Inside Easy Installation Includes Time Clock Text Driven Menu Built-in CO Monitor



Cupboard Fit⁽²⁾ Compatible Out Of The Box Rear Flue 10 Year Warranty with BeSMART⁽¹⁾

GET IN TOUCH
 Vokèra Limited, Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG
E: enquiries@vokera.co.uk **T:** 0844 391 0999
W: www.vokera.co.uk **F:** 0844 391 0998

WE ARE SOCIAL

