









VISIO 4K4017 – BATH TAP PAIR



Finish Chrome Body Brass Fittings Metal backnut & washer Connection 3/4" BSP threaded tail Min dynamic pressure 0.1 Max dynamic pressure 6 Max static pressure 16 Max water temperature 85°C Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications Tested at 0.2 bar	Specification						
Fittings Metal backnut & washer Connection %" BSP threaded tail Min dynamic pressure 0.1 Max dynamic pressure 6 Max static pressure 16 Max water temperature 85°C Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Finish	rome					
Min dynamic pressure 0.1 Max dynamic pressure 6 Max static pressure 16 Max water temperature 85°C Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Body	Bra	Brass				
Min dynamic pressure 0.1 Max dynamic pressure 6 Max static pressure 16 Max water temperature 85°C Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Fittings	etal backnut & washer					
Max dynamic pressure 16 Max static pressure 16 Max water temperature 85°C Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Connection	3SP threaded tail					
Max static pressure 85°C Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Min dyn	ressure	essure 0.1				
Max water temperature Flow rates Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Max dyn	ressure	essure 6				
Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Max static pressure 16					16	
Pressure 0.1 0.5 1 3 L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Max water temperature				85°C		
L/min 10.1 30.1 43.7 78.2 All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications	Flow rates						
All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications 17.9 I/min	Pressure	0.1	0.5	1		3	
Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice. Certifications 17.9 I/min	L/min	10.1	30.1	43.7	7	78.2	
17.9 l/min	Dimensions supplied are nominal and subject to tolerance. Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change						
	Certifications						

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

