





EBRO

4G4122 – MONO BASIN MIXER



					Specification				
				Finish	Cł	Chrome			
				Body	Br	Brass			
			Fittings		Metal plate, wash stud & locking nu				
				Connection		M12 – DN8 flexible ho with ½" BSP threaded			
				Min dynamic pressure			9	0.1	
				Max dynamic pressure 6			6		
153				Max static pressure 1			16		
0				Max water temperature			e	60°C	
					1	Flow rates			
		¥		Pressure	0.1	0.5	1	3	
Ø 55		40 MAX	100 100	L/min	1.6	7.8	12	21.9	
				All Pressures are in Bar.					
				Dimensions supplied are nominal and subject to tolerance.					
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.					
				Performance details are based on trials under test conditions and for guidance only.					
	The Company reserves the right to change								
Features & Benefits				product specification without prior notice. Certifications					
				Certifications					
10 YEAR Guarantee	Low Pressure	Flexible Hose	Flip-Up Waste	4PPROVED PP	WRAS ROVED PRODUCT 4.5 I/min 3021 - Mar 20 Tested at 0.2 bar				
Flow Straightener	Flow Aerator	Single Flow							

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

