





## SIGNIA

## 4L2101 – BASIN TAP PAIR



						Specification				
				Finish	Cł	Chrome				
			Body	Br	Brass					
			Fittings	Me	Metal backnut &		vasher			
			Connection	Connection <sup>1</sup> / <sub>2</sub> " BSP threaded		eaded ta	il			
			Min dynamic pre		ressure		0.1			
			Max dynamic pressure		6					
				Max static pressure 16			16			
				Max water temperature 85°0			85°C			
			<b>D</b>	1	rates	1				
	XWH SE		R	Pressure	<b>0.1</b> 6.7	<b>0.5</b> 21.5	<b>1</b> 31.6	<b>3</b> 57.2		
				All Pressures are in Bar.						
				Dimensions supplied are nominal and subject to tolerance.						
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.						
				Performance details are based on trials under test conditions and for guidance only.						
				The Company reserves the right to change product specification without prior notice.						
Features & Benefits				Certifications						
10 YEAR Guarantee	Low Pressure	Inlet Tail	Flow Straightener	W thener 1507026 - July 20 Tested at 0.2 bar						
			ou digittorior	1507020 - J	uly 20	Tes		.2 vai		
Single Flow										

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

