





SIGNIA

4L2105 – DECK MOUNTED BSM



				Specification				
				Finish	Finish Chrome			
				Body	Br	Brass		
				Fittings	Me	Metal backnut &		vasher
				Connection ³ / ₄ " BSP threaded t			eaded ta	il
				Min dynamic pres		ressure		0.1
				Max dynamic pres		oressure		6
				Max st	essure	ssure 2		
			Max water temperature			60°C		
Market Contraction of the Contra		Ÿ 105		Flow rates				
				Pressure	0.1	0.5	1	3
j	79		6	L/min	9.1	32.4	47.7	85.3
				All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance.				
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.				
				Performance details are based on trials under test conditions and for guidance only.				
				The Company reserves the right to change product specification without prior notice.				
Features & Benefits				Certifications				
10 YEAR Guarantee	Low Pressure	Inlet Tail	Flow Straightener	• 18.5 Tested at 0				
Shower Kit Included	Single Flow							

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

