







STRATA 4K6003 – TALL MONO BASIN

				Specification				
			Finish	Cł	Chrome			
			Body Brass					
			Fittings	Fittings Metal plate, wash stud & locking nu				
			Connection	Connection M12 – DN8 flexible hoses with ½" BSP threaded ends				
			Min dynamic pressure 0.1			0.1		
			Max dynamic pressure 6					
				Max static pressure 16			16	
			Max water temperature 60°C			60°C		
					Flow rates			
				Pressure	0.1	0.5	1	3
	302		847	L/min	1.1	5.9	9.1	17.2
				All Pressures are in Bar.				
				Dimensions supplied are nominal and subject to tolerance.				
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.				
115				Performance details are based on trials under test conditions and for guidance only.				
				The Company reserves the right to change product specification without prior notice.				
Features & Benefits				Certifications				
10 YEAR Guarantee	Low Pressure	Flexible Hose	Click Waste	APPROVED P1 1704325 - /	RODUCT		3.4 I, ted at 0	
Flow Straightener	Flow Aerator	Single Flow						

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

