







## TEMPEST 4K7104 – BATH AND SHOWER MIXER

	Specification				
	Finish	Chrome	Chrome		
	Body	Brass			
	Fittings	Metal backnut & was		vasher	
	Connection	¾" BSP threaded t		il	
	Min dynan	Min dynamic pressure		0.1	
	Max dynar	Max dynamic pressure		6	
	Max stati	Max static pressure		25	
	Max water	Max water temperature		60°C	
		Flow rates	I		
		0.1 0.5	1	3	
160	L/min 1	1.1 25.1	35.6	60	
	Dimensions supp	All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance.			
	Inclusion of aerat	Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow			
		Performance details are based on trials under test conditions and for guidance only.			
	The Company reproduct specifica				
Features & Benefits	Ce	ertificatior	IS		
10 YEAR GuaranteeL Low PressureImage: Comparison of the second secon	• 15.8 l/l Tested at 0.2				
Flow Aerator Shower Kit Included Single Flow					

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

