



STRATA BLADE 4K6053 – MINI MONO BASIN



				Specification				
				Finish	Ch	Chrome		
				Body	Bra	Brass		
				Fittings		Metal plate, washer, stud & locking nut		
						12 – DN8 flexible hoses th ½" BSP threaded ends		
				Min dyn	pressure		0.1	
				Max dynamic pressure 6				6
				Max static pressure				16
			Max water temperature			e	60°C	
			D	1	Flow rates			
				Pressure	0.1 1.7	0.5 6.5	1 9.8	3 18.2
				All Pressures are in Bar. Dimensions supplied are nominal and subject to tolerance.				
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.				
				Performance details are based on trials under test conditions and for guidance only.				
				The Company reserves the right to change product specification without prior notice.				
Features & Benefits					Certifi	cation	IS	
10 YEAR Guarantee	Low Pressure	Flexible Hose	Click Waste	APPROVED PF	RODUCT		5.3	l/min
				1704392 - A	April 22	Tes	ted at (0.2 bar
Flow Straightener	Flow Aerator	Single Flow						

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

