

Г







SEQUEL 478001 – MONO BASIN MIXER

	Specification								
A LOT ALL ALL ALL ALL ALL ALL ALL ALL ALL AL				Finish	Cł	Chrome			
				Body	Body Bi		Brass		
				Fittings	Fittings Metal plate, wash stud & locking nu				
				Connection	Connection M12 – DN8 flexible hoses with ½" BSP threaded ends				
a starter and a starter and a starter a starte	Min dynamic pressure 0.			0.1					
A Carlos and a car				Max dynamic pressure			9	6	
171				Max st	essure	sure			
XVM SP			Max wat	er tem	emperature		60°C		
				Flow	Flow rates				
	Ø 63		•	Pressure	0.1	0.5	1	3	
_				L/min	5.7	20.2	30.2	54.1	
				All Pressures are in Bar. Dimensions supplied are nominal and subject					
				to tolerance.					
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.					
	Performance details are based on trials under test conditions and for guidance only.								
	The Company reserves the right to change product specification without prior notice.								
Features & Benefits				Certifications					
10 YEAR Guarantee	Low Pressure	Pop-up Waste	Flexible Hose	♦ 11.4 Tested at 0					
Flow Straightener	Flow Aerator	Single Flow							

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

