

Γ







SEQUEL 479001 – MONO BIDET MIXER

	Specification								
a more a de la companya de la				Finish	Ch	Chrome			
				Body	Br	Brass			
				Fittings	Metal plate, wash stud & locking nut				
					Connection M12 – DN8 flexible hoses with ½" BSP threaded ends				
					Min dynamic press			0.1	
					Max dynamic pressure			6	
					Max static pressure			16	
				Max wat	er tem	emperature		60°C	
				Flow	Flow rates				
				Pressure	0.1	0.5	1	3	
61		~		L/min	0.9	7.1	11	20.3	
				All Pressures are in Bar.					
				Dimensions supplied are nominal and subject to tolerance.					
				Inclusion of aerator (if supplied) or restrictors (sold separately unless stated) will affect flow rate result.					
				Performance details are based on trials under test conditions and for guidance only.					
					The Company reserves the right to change product specification without prior notice.				
Features & Benefits				Certifications					
10 YEAR Guarantee	L v Pressure	Pop-up Waste	Flexible Hose	3 .5 I	/min				
		24 82		Tested at 0).2 bar				
Flow Aerator Sir	igle Flow								

COMAP UK Ltd. Unit C6, William Way, Moss Ind Est, St Helens Rd, Leigh. Lancashire. WN7 3PT www.comaptaps.co.uk

