# HYDROPOWER Power Shower Range

## HY POWSHX10 W

Hydropower Power Shower 1000 XT White





#### Features:

- Thermostatic control keeps water temperature within +/-1°C
- Supplied with rub clean handset, hose and riser kit

Specification				
Finish/Colour:	White			
Main Construction Material:	ABS Plastic			
No of Controls:	2			
Shower Type:	Power Shower			
Shower Head Type:	Adjustable			
Working Pressure Range: (bar)	Min. 0.1 Bar, Max. 1.0 Bar			
Maximum Static Pressure: (bar)	10			
Plumbing System Suitability:	Low Pressure Gravity System Only			
Connection Inlet:	15mm Push-Fit			
Connection Outlet:	G 1/2"			
Thermostatic:	Thermostatic			
Maximum Hot Water Supply:	65			
Power Rating:	230V AC@50Hz/150W			
Motor Rating:	15 Minutes			

### Dimensions (measurements in mm)





**TAPS & SHOWERS** 

D5

#### **Product Certifications:**

BEAB Certificate No: 20618 BEAB Expiry Date: 18/03/2021



Ce

For more products, visit our website <a href="http://www.bristan.com">http://www.bristan.com</a>



TECH DATA

s, visit our website: <u>n.com</u>						
	Flow Rates (I/min)					
	System Pressure (bar)	0.03	0.1	0.5		
	Through Handset (Both Rings)	7.9	8.2	9.3		
NICAL	Real France P	B	RISTA			

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.