



IT'S SO GOOD WE PUT OUR NAME ON IT

The **ONLY TUBE** You Need

- **Multi-use** for All Trades
- Perfect for **Sanitaryware**, Tiles, Mirrors, Metals, Wood, Stone, Concrete, Marble & Brick
- Seals and Bonds
- Fills and Fixes
- Anti Mould
- Waterproof
- Durable
- Fast Curing
- **No Solvents** or Isocyanates



The only sealant **Tested and Approved** for use with **McAlpine Plumbing Products**

Available in **Brilliant White & Super Clear**

BRILLIANT WHITE
MACXSEAL-WH

SUPER CLEAR
MACXSEAL-CL



ANTI-FUNGAL



DURABLE



FAST CURING



HIGH STRENGTH GRAB



BONDS IN THE WET



INTERNAL AND EXTERNAL USE



LOW ODOUR



SOLVENT FREE



PAINTABLE



UNIQUE FORMULA



MACXSEAL PRODUCT FEATURES

MacXseal is a Sealant and adhesive in one. A toolbox in a tube.

WHERE DO YOU START?

So many products out there promise that they will do this, they will do that, they are the new wonder sealant, they are based on a brand new technology, with a fancy new name.

We are here to tell you much of that is utter nonsense. So, if that's the case why did **McAlpine Plumbing** create their own product?

IT'S TO DO WITH ACETOXY

The name Acetoxy comes from the fact that the compound releases acetic acid. You'll know it from the strong vinegar like smell while curing. When acetoxy is used with a fitting, it causes a degradation in the plastic which causes it to splinter and break. In simple terms it's plastic decay. This breakdown leads to stress cracking, which leads to leaks.

Our reputation is built on **not compromising** on the quality of our products. We test them to destruction. So we decided to test sealants and adhesives, to see what would work. And then one of our Sales Managers said *'Why not create our own and make sure it works for all our products.'* Seemed like a good idea. So MacXseal was born. It's now the only sealant Tested and Approved for use with McAlpine Plumbing Products.

SEALANT	✓
ADHESIVE	✓
TESTED: SAFE FOR USE WITH MCALPINE PRODUCTS	✓
UV STABILISER NO DISCOLOURING	✓
CONTAINS FUNGICIDE	✓
CURING TIME	Approx 3mm per 24Hrs at 23°C & 50% Humidity
SKIN TIME	15-20 mins at 23°C & 50% Humidity
TENSILE STRENGTH	(DIN 53504-52)(E Modulus at break) White 2.10 N/mm2 Clear 1.69 N/mm2 (ISO 11600) White 0.6 N/mm2 Clear 0.6 N/mm2
ODOUR	LOW
WATERPROOF	✓
CONTAINS SOLVENTS OR ISOCYANATES	X
USED ON ALL REASONABLE SURFACES	✓
PAINTABLE	✓
APPLICATION TEMP RANGE	5° TO 35°
SERVICE TEMP RANGE	-40°C to +100°C
SHORE A HARDNESS	45 -55 (DIN 53505)
MOVEMENT ACCOMMODATION	±20%
FLOW	<2mm (ISO 7390)
INTERNAL & EXTERNAL USE	✓
BONDS IN THE WET	✓
UNIQUE FORMULA	✓



**AVAILABLE FROM
ALL GOOD STOCKISTS**

Visit www.mcalpineplumbing.com/macxseal for further information