## PRISM Tap Range Prism Floor Standing Bath Shower Mixer Chrome

D5

# PM FSBSM C



#### Features:

- Long life ceramic cartridge for added durability and ease of use
- Easy to use lever handle
- Includes 1.5m hose and rubclean anti-limescale handset
- Minimum working pressure of 2.0 bar

### **Product Certifications:**




For more products, visit our website: http



Specification			
Product Type:	Taps		
Main Construction Material:	Brass		
Mount Type:	Wall		
Handle Type:	Lever		
Connection Inlet:	1/2" BSP		
Connection Outlet:	G 1/2"		
Number of Tap Holes:	N/A		
Valve/Cartridge Type:	40mm Single Lever Cartridge		
Plumbing System Requirements:	Suitable for all plumbing systems		
Minimum Dynamic Pressure (bar):	2 bar		
Maximum Dynamic Pressure (bar):	5 bar		
Maximum Hot Water Temperature °C:	65°C		
Maximum Static Pressure (bar):	10 bar		
Flow Type:	Single		
Isolation Included:	No		

#### Dimensions (measurements in mm)



p://www.bristan.com					
	Flow Rates (I/min)				
	System Pressure (bar)	2	3	5	
	Through Bath Filler (mixed)	21.1	25.9	33.4	
	Through Handset (mixed)	14	17.1	22.1	
TECHNICAL DATA SHEET	P D ALLA VEARS LO VEARS	В	RIST	AN	

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

\* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.