## SFF PROSNK BN

## SAFFRON Tap Range Saffron Professional Sink Mixer Brushed Nickel



		res:
_	$\sim$	raci
	-c	11 – 5

- Long life ceramic cartridge for added durability and ease of use
- Metal fixing nut for added durability
- Minimum working pressure of 1.5 bar
- Flexible tails included
- Particular attention should be paid to this product which will need to be installed in accordance with your local Water Authority/Water Regulations

## **Product Certifications:**






For more products, visit our website: http://www.bristan.com



Specification					
Product Type:	Kitchen Taps				
Main Construction Material:	Brass				
Mount Type:	Deck Mounted				
Handle Type:	Lever Handle				
Connection Inlet:	1/2" BSP Flexible Tails				
Connection Outlet:	Aerator				
Number of Tap Holes:	1				
Valve/Cartridge Type:	35mm Cartridge				
Plumbing System Requirements:	Suitable for high pressure systems				
Minimum Dynamic Pressure (bar):	1.5 bar				
Maximum Dynamic Pressure (bar):	5.0 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single Flow				
Isolation Included:	No				

Dimensions (measurements in mm)



Flow Rates (I/min)								
System Pressure (bar)	1.5	2	3	4	5			
SFF PROSNK BN (mixed)	5.1	5.9	7.2	8.3	9.3			

## TECHNICAL DATA SHEET



