HOU BAS BLK

HOURGLASS Tap Range Hourglass Basin Mixer Black



Features:

- You really can count on Bristan taps as they are designed, engineered and tested to last with our precise glide and secure fix components plus a modern black finish, all under a 10 Year guarantee for peace of mind
- A black finish that will make a statement in any bathroom
- All in one box Includes flexible tails and clicker waste so nothing to buy separately
- Long life ceramic cartridge for added durability and ease of use
- Supplied with metal fixing nut for added durability and to secure your tap in place
- Flexible tails included

Product Certifications:





♦ 5 l/min

For more products, visit our website: http://www.bristan.com

Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck Mounted			
Handle Type:	Lever Handle			
Connection Inlet:	M10 Flexible Tails			
Connection Outlet:	M24 5lpm Flow Limiter			
Number of Tap Holes:	1			
Valve/Cartridge Type:	35mm Single Lever Cartridge			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5.0 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single Flow			
Isolation Included:	No			

Dimensions (measurements in mm)





	Flow Rates (I/min)							
	System Pressure (bar)	0.2	0.5	1	2	3	5	
IN 2424	HOU BAS BLK (mixed)	5	5	5	5	5	5	
TECHNICAL DATA SHEET	or QUALLA Stranster ARAINTER ARAINTER ARAINTER *		B	RIS	3 7/		D2	

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.