APE BF C

APELO Tap Range Apelo Bath Filler Chrome



| Specification | | | | |
|-----------------------------------|------------------------------------|--|--|--|
| Product Type: | Bathroom Taps | | | |
| Main Construction Material: | Brass | | | |
| Mount Type: | Deck | | | |
| Handle Type: | Long Angled | | | |
| Connection Inlet: | 3/4" BSP | | | |
| Connection Outlet: | Housed M24 Aerator | | | |
| Number of Tap Holes: | 2 | | | |
| Valve/Cartridge Type: | 3/4" Short Stem Ceramic Disc Valve | | | |
| Plumbing System Requirements: | Suitable for all plumbing systems | | | |
| Minimum Dynamic Pressure (bar): | 0.2 bar | | | |
| Maximum Dynamic Pressure (bar): | 5 bar | | | |
| Maximum Hot Water Temperature °C: | 60°C | | | |
| Maximum Static Pressure (bar): | 10 bar | | | |
| Flow Type: | Single | | | |
| Isolation Included: | No | | | |

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black.
- Co-ordinating Bathroom taps available.

Product Certifications:



WRAS Certificate No: 2309905 WRAS Expiry Date: 30/09/2028

For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm) 140 105 230 65 180

| Flow Rates (I/min) | | | | | | | |
|-----------------------|------|------|------|------|----|-------|--|
| System Pressure (bar) | 0.2 | 0.5 | 1 | 2 | 3 | 5 | |
| APE BF C (mixed) | 24.2 | 40.4 | 57.2 | 80.9 | 99 | 127.9 | |

TECHNICAL DATA SHEET



