APE BSM C

APELO Tap Range Apelo Bath Shower Mixer Chrome



Specification	
Product Type:	Bathroom Taps
Main Construction Material:	Brass
Mount Type:	Deck
Handle Type:	Long Angled
Connection Inlet:	3/4" BSP
Connection Outlet:	Housed M24 Aerator
Number of Tap Holes:	2
Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve
Plumbing System Requirements:	Suitable for all plumbing systems
Minimum Dynamic Pressure (bar):	0.3 bar
Maximum Dynamic Pressure (bar):	5 bar
Maximum Hot Water Temperature °C:	60°C
Maximum Static Pressure (bar):	10 bar
Flow Type:	Single
Isolation Included:	No

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Rub clean handset limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black, brushed brass and gun metal grey.
- Co-ordinating Bathroom taps available.

Dimensions (measurements in mm) 140 230 850 180 95 210

Product Certifications:





Kiwa Certification No: 2312719 Kiwa Expiry Date: 11/12/2028

WRAS Certification No: 2312357 WRAS Expiry Date: 31/12/2028





Flow Rates (I/min) System Pressure (bar) 0.3 0.5 2 5 Through Bath Filler (mixed) 12.5 16.4 33.3 40.8 52.6 24 Through Handset (mixed) 3.9 5.2 11.2 14.3 19 7.6

TECHNICAL DATA SHEET



