FRM BSM C

FRAMMENTO Tap Range

Frammento Bath Shower Mixer Chrome



	Specification			
	Product Type:	Bathroom Taps		
	Main Construction Material:	Brass		
	Mount Type:	Deck		
	Handle Type:	Flat Angled		
	Connection Inlet:	3/4" BSP		
	Connection Outlet:	M24 Recessed Honeycomb Aerator		
	Number of Tap Holes:	2		
4.4	Valve/Cartridge Type:	3/4" Short Stem Ceramic Disc Valve		
l	Plumbing System Requirements:	Suitable for all plumbing systems		
	Minimum Dynamic Pressure (bar):	0.3 bar		
ı	Maximum Dynamic Pressure (bar):	5 bar		
ı	Maximum Hot Water Temperature °C:	60°C		
	Maximum Static Pressure (bar):	10 bar		
	Flow Type:	Single		
	Isolation Included:	No		

Dimensions (measurements in mm)

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years.
 Salt spray tested to ensure added durability.
- Rub clean handset limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.
- 10-year parts and 1 year labour guarantee for peace of mind.
- Also available in black, brushed brass and gun metal.
- Co-ordinating Bathroom taps available.

Product Certifications:







Kiwa Certification No: 2312720 Kiwa Expiry Date: 11/12/2028

WRAS Certification No: 2312356 WRAS Expiry Date: 31/12/2028









230

Flow Rates (I/min)									
System Pressure (bar)	0.3	0.5	1	2	3	5			
Through Bath Filler (mixed)	9.6	15.8	23.4	33.4	40.7	52.5			
Through Handset (mixed)	3.9	5.1	7.5	11	14	18.6			

TECHNICAL DATA SHEET



