



## Product

- HPBV11 - 1" Female Swivel x 1" Male Extended Lever Ball Valve
- HPBV114 - 1 1/4" Female Swivel x 1" Male Extended Lever Ball Valve
- HPBV114X2 - 1 1/4" Female Swivel x 1 1/4" Male Extended Lever Ball Valve
- HPBV28 - 1" Female Swivel x 28mm Extended Lever Ball Valve
- HPBV35 - 1 1/4" Female Swivel x 35mm Extended Lever Ball Valve
- EXTKIT - Lever Ball Valve Extension Kit

## Technical Specification

Max Inlet Pressure (static):	25 Bar
Working Temperature:	-10 to 90°C
Temperature Range:	-20 to 120°C
Thread Standard:	ISO228

	A	B	C	D	E	F	G
HPBV11	1"	1"	88.6	115	115.4	95.3	40
HPBV114	1"	1 1/4"	89	115	121	95.3	40
HPBV114X2	1 1/4"	1 1/4"		115			40
HPBV28	28mm	1"	93.25	115		95.3	40
HPBV35	35mm	1 1/4"	101	115		101.8	40

## Additional Information

**Solid brass construction**

**Extended lever ball valve handle for easy access, even with insulation**

**Pressure rating of PN25**

**Working temperature range of -10 to 90°C**

**ISO228 threads**

