# VT2 BF C

### VANTAGE Tap Range Vantage 2 Bath Filler Chrome



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck Mounted			
Handle Type:	Lever Handle			
Connection Inlet:	3/4" BSP			
Connection Outlet:	M24 Aerator			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single Flow			
Isolation Included:	No			

#### Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability

#### Product Certifications:



WRAS Certificate No: 250403304 WRAS Expiry Date: 30/04/2030





**♦** 94.1 l/min

For more products, visit our website: http://www.bristan.com



### Dimensions (measurements in mm)





Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
VT2 BF C (mixed)	24.3	38.4	54.3	76.8	94.1	121.5		

## TECHNICAL DATA SHEET



