

Product Finish: Antique Brass

Product code: AT2222
EAN13 barcode: 5060879994461



Product features:

Victorian inspired aesthetic

Quarter turn handle action for precise flow control

Ceramic handle(s) as standard

Flow Limited to 5 Litres per Minute for Part G compliance


Supplied complete with flexible tail pipes for fast simple fitting

Additional information / Parts included:

Includes additional Honeycomb 1.5gpm, Solid metal handle addition

Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product dimensions:



- **Overall, Height / projection:** 385 mm
- **Exit reach:** 223 mm
- **Exit height:** 237 mm
- **Centre distance(s):**

- **Base diameter(s):** 60 mm
- **Recommended hole diameter:** Ø 35 mm
- **Max. surface depth:** 50 mm

- **Spout diameter:** 20 mm
- **Spout aerator size:** M22 x 1

Packaged properties:

Box length: 435mm

Box depth: 70mm


Box width: 340mm

Units per outer: 5

Tap only weight: 1.88kg

Boxed weight: 2.79kg

Product flow characteristics:



- **Min / Max water pressure:** 0.30 / 5 bar
- **Recommended / Max water temperature:** 46°C / 70°C
- **Part G - Mixed flow rate at 3 bar (litres / min):** 17.80

- **Control valve type:** Ceramic disc QT
- **Product flow characteristics:** Single flow
- **Non return valve(s):** None

- **Aerator type:** Honeycomb Aerator
- **Accepts revolve / spray areator:** No
- **Spout connection method:** Grub screw

- **Tail pipe inlet / outlet size:** M12 / 1/2" BSP Female
- **Inlet pipe type / length:** Flexible stainless braided hose / 250 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year