Deck Mounted Panel Valves






Product features:

- Quarter turn handle action for precise flow control
- Luscious European quality chromium plate finish
- · Modern minimalism with flair
- · Metal construction throughout
- · Unique and coordinated diamond quilted handle design

Packaged properties:

Box length (mm): 0 Box depth(mm): 0 Box width(mm): 0 Boxed weight (Kg): 0.00 Includes pop up waste?: No **Additional comments:**

Product dimensions:




• Product mounted where: Surface • Recommended hole size: $0 \, \text{mm}$

• Overall Height / projection: 56 mm • Exit reach: 0 mm • Exit height: 0 mm · Base size: 55 mm

• Inlet centre distance(s): n/a mm

• Min. fitting depth required: 30 mm · Max. surface depth: n/a

Product flow characteristics:



- Min / Max water pressure (bar): 0.20* / 5
- Part G max. mixed flow rate at 3 bar (I/m): 49.92
- Inlet connection type / length: Flexible / 300 mm
- Inlet (plumbing connection) / outlet size: 1/2" F / 1/2" F
- Product flow characteristics: N/a

Non return valve(s) supplied or position: None

• Aerator type: N/a

• Control valve type: 1/2" QT CD (7.5 x 22)

• Includes output diverter?: No

• Inlet meshed particle filters included: n/a

• Shower hose type / length: N/a / n/a

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives